



Detcon Model AV2-C1D1M

ISO 9001: 2008
Certified

888-367-4286
281-367-4100
fax 281-292-2860

www.detcon.com
sales@detcon.com

Hazardous Duty Alarm Station Class 1, Division 1 Multitone

Description

Detcon Model AV2-C1D1M audio visual alarm stations are designed for installation and use in heavy industrial environments including offshore applications where compliance with ABS standards are required. The alarm station consists of a combination of two warning lights and a siren. Warning lights can consist of any combination of dome colors such as amber, blue, clear, green, red, or magenta. The audible alarm features 3 field selectable tones: Wail, Yelp, and Horn. Model AV2-C1D1M alarm assemblies are specifically designed for hazardous locations or corrosive environments where a very bright visual and high decibel alarm signal is required. The high-intensity strobe lights provide 85 flashes per minute. The siren produces a noise level of 98dbA @ 10 feet in a wide angle sound dispersion pattern. The lights are UL listed for Class I, Division 1, Groups C and D; Class II, Groups E, F, and G; and Class III. The siren is UL listed for Class I, Groups B, C and D.

Model AV2-C1D1M alarm components are pre-assembled and mounted on a T-shaped epoxy painted aluminum bracket with pre-drilled mounting holes that accommodate U-bolts and up to 3" diameter pipe stands. The assemblies are NEMA 4X rain tight and suitable for installation in harsh locations. Overall dimensions are 39"H x 30"W x 18.5"D.



Ordering Information

977- 6 00-03

Qty. of Strobes
1 - 1 2 - 2

Color of 1st Strobe
Color of 2nd Strobe
2 - Red 6 - Blue
4 - Amber 7 - Magenta
5 - Green 9 - Clear

Voltage
2 - 24 VDC
3 - 120 VAC
4 - 240 VAC

Light Specifications

- Voltage:** 24VDC, 120VAC 50/60HZ, 240VAC 50/60HZ
- Mount:** Flange
- Operating Current:** 1.9 Amps at 24VDC, 1.14 Amps at 120VAC, 0.7 Amps at 240VAC
- Dome Colors:** Amber, Blue, Clear, Green, Magenta, Red
- Dome Guard:** Included
- Operating Temperature Minimum:** -40°C
- Operating Temperature Maximum:** 55°C
- Flash Rate/Minute:** 85
- Effective Candle Power:** 200 eff. (clear dome)
- Height:** 13.69 in.
- Diameter:** 7.44 in.
- Warranty:** 1 Year

Siren Specifications

- Voltage:** 24VDC, 120VAC 50/60HZ, 240VAC 50/60HZ
- Mount:** Omni Directional Mounting Bracket
- Operating Current:** 0.6Amps at 24VDC, 0.21 Amps at 120VAC, 0.12 Amps at 240VAC
- Temperature Rating:** -35°C to +72°C; -31°F to +161°F
- Sound Output @ 10 '(UL Audibility Rating):**
 - Wail: 98 dbA
 - Yelp: 99 dbA
 - Horn: 95 dbA
- Enclosure Rating:** Type 3R, IP44
- Dimensions:** 14.75"H x 8.88"W x 14.75"D
- Warranty:** 1 Year

www.detcon.com